



SP-200PA

Order No.: 10.2960

Price upon request

PRODUCTINFOS

PA and power bass-midrange speaker, 100 W, 8 Ω

TECHNICAL SPECIFICATIONS

SP-200PA

Impedance (Z)	8 Ω
Frequency range	f3-4,000 Hz
Resonant frequency (fs)	55 Hz
Power rating	100 W
Peak music power output	200 W
Sensitivity	91 dB/W/m
Suspension compl. (Cms)	0.64 mm/N
Moving mass (Mms)	13 g
Mech. Q factor (Qms)	3.42
Electr. Q factor (Qes)	0.99
Total Q factor (Qts)	0.77

SP-200PA

Equivalent volume (Vas)	39 l
DC resistance (Re)	6.9 Ω
Force factor (BxL)	5.6 Tm
Voice coil induct. (Le)	0.5 mH
Voice coil diameter	\varnothing 25 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	\pm 3.75 mm
Eff. cone area (Sd)	214 cm ²
Magnet weight	570 g
Magnet diameter	\varnothing 100 mm
Mounting cutout	\varnothing 182 mm
Mounting depth	90 mm
Dimensions	\varnothing 202 mm x 90 mm
Outside diameter	\varnothing 202 mm
Width	202 mm
Depth	90 mm
Admiss. ambient temp.	0-40 °C
Weight	1.255 kg
Sales unit	1
Type of speaker	8"