



SP-60/8

Order No.: 10.0740

Price upon request

PRODUCTINFOS

Hi-fi bass-midrange speakers, 30 W, 8 Ω (/8) and 4 Ω (/4)

- Drilled pole core
- Good frequency response linearity
- For small speaker systems in the hi-fi range

TECHNICAL SPECIFICATIONS

SP-60/8

Impedance (Z)	8 Ω
Frequency range	f3-8,000 Hz
Resonant frequency (fs)	65 Hz
Power rating	30 W
Peak music power output	60 W
Sensitivity	90 dB/W/m

SP-60/8

Suspension compl. (Cms)	0.8 mm/N
Moving mass (Mms)	4 g
Mech. Q factor (Qms)	2.10
Electr. Q factor (Qes)	0.64
Total Q factor (Qts)	0.49
Equivalent volume (Vas)	6 l
DC resistance (Re)	6.5 Ω
Force factor (BxL)	4.1 Tm
Voice coil induct. (Le)	0.3 mH
Voice coil diameter	\varnothing 25,5 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	\pm 2 mm
Eff. cone area (Sd)	55 cm ²
Magnet weight	280 g
Magnet diameter	\varnothing 80 mm
Mounting cutout	\varnothing 96 mm
Mounting depth	60 mm
Dimensions	105 x 105 x 60 mm
Width	105 mm
Height	105 mm
Depth	60 mm
Admiss. ambient temp.	0-40 °C
Weight	0.654 kg
Sales unit	1
Type of speaker	4"