



SPP-110/4

Order No.: 10.1050

Price upon request

PRODUCTINFOS

Hi-fi bass-midrange speakers, 30 W, 4 Ω

- Carbonised plastic cone
- Drilled pole core
- Linear wide frequency response in very small cabinets

HOBBY HiFi 03/2016

"Ideally suited for the combination with ribbon tweeters and magnetostatic tweeters."

TECHNICAL SPECIFICATIONS

SPP-110/4

Impedance (Z)	4 Ω
Frequency range	f3-8,000 Hz

SPP-110/4

Resonant frequency (fs)	53 Hz
Power rating	30 W
Peak music power output	60 W
Sensitivity	90 dB/W/m
Suspension compl. (Cms)	1.95 mm/N
Moving mass (Mms)	4.3 g
Mech. Q factor (Qms)	2.01
Electr. Q factor (Qes)	0.46
Total Q factor (Qts)	0.37
Equivalent volume (Vas)	8 l
DC resistance (Re)	3.3 Ω
Force factor (BxL)	3.3 Tm
Voice coil induct. (Le)	0.3 mH
Voice coil diameter	25.5 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	± 2 mm
Eff. cone area (Sd)	55 cm ²
Magnet weight	280 g
Magnet diameter	\varnothing 80 mm
Mounting cutout	\varnothing 100 mm
Mounting depth	59 mm
Mounting hole diameter	\varnothing 120 mm
Hole spacing X-axis	84.5 mm
Hole spacing Y-axis	84.5 mm
Dimensions	110 x 110 x 60 mm
Outside diameter	\varnothing 135 mm
Width	110 mm
Height	110 mm
Depth	60 mm
Admiss. ambient temp.	0-40 °C
Weight	0.809 kg
Sales unit	1
Type of speaker	4"