



Specifications for the **LT<sup>®</sup>1195** have been modified as shown below in **bold**. For complete specifications, typical performance characteristics and applications information, please see the **LT1195** data sheet.

 LTC and LT are registered trademarks of Linear Technology Corporation.

## **±5V ELECTRICAL CHARACTERISTICS** $T_A = 25^\circ\text{C}$

$V_S = \pm 5\text{V}$ ,  $C_L \leq 10\text{pF}$ , pin 5 open circuit, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS	LT1195M/C			UNITS
			MIN	TYP	MAX	
$t_{r1}$ , $t_{f1}$	Rise Time, Fall Time	$A_V = 50$ , $V_{OUT} = \pm 1.5\text{V}$ , 20% to 80% (Note 9)	125	170	<b>285</b>	ns

**Note 9:** AC parameters are 100% tested on the ceramic and plastic DIP packaged parts (J8 and N8 suffix) and are sample tested on every lot of the SO packaged parts (S8 suffix).

For further information regarding this specification notice contact:

Linear Technology Corporation  
1630 McCarthy Blvd.  
Milpitas, California 95035-7417  
Attn: Product Marketing Manager  
Phone: (408) 432-1900