


Central
Semiconductor Corp.
Central
Semiconductor Corp.
Central
Semiconductor Corp.
Central™
Semiconductor Corp.

145 Adams Avenue
Hauppauge, New York 11788



1N3938 THRU 1N3942

2.0 AMP SILICON RECTIFIER
200 THRU 1000 VOLTS

JEDEC DO-13 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 1N3938 series types are silicon rectifiers mounted in a hermetically sealed metal case designed for controlled avalanche applications. Special selections are available on special order. Please consult factory.

MAXIMUM RATINGS (TA=25°C)

	SYMBOL	1N3938	1N3939	1N3940	1N3941	1N3942	UNIT
Peak Repetitive Reverse Voltage	VRRM	200	400	600	800	1000	V
DC Blocking Voltage	VR	200	400	600	800	1000	V
Average Forward Current	IO				2.0		A
Peak Forward Surge Current (One Cycle)	IFSM				30		A
Operating and Storage Junction Temperature	TJ, TSTG			-65 to +200			°C

ELECTRICAL CHARACTERISTICS (TA=25°C)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
VF	IF=2.0A (1N3938, 1N3939, 1N3940)		1.1	V
VF	IF=2.0A (1N3941, 1N3942)		1.5	V
IR	VR=Rated VRRM		200	µA
BVR	IR=50µA (1N3938)	240	600	V
BVR	IR=50µA (1N3939)	480	900	V
BVR	IR=50µA (1N3940)	720	1150	V
BVR	IR=50µA (1N3941)	960	1350	V
BVR	IR=50µA (1N3942)	1160	1550	V

Central™
Semiconductor Corp.

145 Adams Avenue
Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824
www.centralsemi.com