


Central
Semiconductor Corp.

Central
Semiconductor Corp.

Central
Semiconductor Corp.

CentralTM
Semiconductor Corp.

145 Adams Avenue
Hauppauge, New York 11788



1N816

FORWARD REFERENCE DIODE
(STABISTOR)

JEDEC D0-35 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 1N816 is a Silicon Forward Reference Diode designed for low level voltage regulating applications where a stabistor is required.

MAXIMUM RATINGS

	<u>SYMBOL</u>		<u>UNIT</u>
DC Power Dissipation [*] Operating and Storage Junction Temperature	P_D	400	mW
	T_J, T_{stg}	-65 TO +175	°C

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}C$ unless otherwise noted)

	<u>SYMBOL</u>	<u>TEST CONDITIONS</u>	<u>MIN</u>	<u>MAX</u>	<u>UNIT</u>
Forward Reference Voltage	V_F	$I_F=1.0mA$	0.58	0.70	VOLTS
Forward Reference Voltage	V_F	$I_F=100mA$		1.0	VOLTS
Reverse Leakage Current	I_R	$I_R=4.0V$		0.1	μA
Peak Reverse Voltage	BV_R	$I_R=100\mu A$	40		VOLTS

1.

2.

LEAD CODE

Lead 1 - Cathode
Lead 2 - Anode

^{*} $T_L=30^{\circ}C$, Lead Length=.375"

CentralTM
Semiconductor Corp.

145 Adams Avenue
Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824
www.centralsemi.com