

International
IR Rectifier

MBRB3030CTL

SCHOTTKY RECTIFIER

30 Amp

Major Ratings and Characteristics

| Characteristics | Values | Units |
|---|------------|------------|
| $I_{F(AV)}$ Rectangular waveform | 30 | A |
| V_{RRM} | 30 | V |
| I_{FSM} @ $t_p = 5 \mu s$ sine | 1100 | A |
| V_F @ 15A pk, $T_J = 125^\circ C$ (per leg) | 0.34 | V |
| T_J range | -55 to 150 | $^\circ C$ |


Description/Features

This center tap Schottky rectifier has been optimized for very low forward voltage drop, with moderate leakage. The proprietary barrier technology allows for reliable operation up to $150^\circ C$ junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.


- $150^\circ C$ T_J operation
- Center tap configuration
- Very low forward voltage drop
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability

Case Styles

MBRB3030CTL



D²PAK



Voltage Ratings

| Parameters | MBRB3030CTL |
|---|-------------|
| V_R Max. DC Reverse Voltage (V) | 30 |
| V_{RWM} Max. Working Peak Reverse Voltage (V) | |

Absolute Maximum Ratings

| Parameters | Values | Units | Conditions |
|---|--------|-------|--|
| $I_{F(AV)}$ Max. Average Forward Current (Per Leg) * See Fig. 5 (Per Device) | 15 | A | 50% duty cycle @ $T_C = 121^\circ\text{C}$, rectangular wave form |
| | 30 | | |
| I_{FSM} Max. Peak One Cycle Non-Repetitive Surge Current (Per Leg) * See Fig. 7 | 1100 | A | 5 μs Sine or 3 μs Rect. pulse 10ms Sine or 6ms Rect. pulse |
| | 360 | | |
| E_{AS} Non-Repetitive Avalanche Energy (Per Leg) | 22.4 | mJ | $T_J = 25^\circ\text{C}$, $I_{AS} = 3\text{Amps}$, $L = 3\text{mH}$ |
| I_{AR} Repetitive Avalanche Current (Per Leg) | 3 | A | Current decaying linearly to zero in 1 μsec Frequency limited by T_J max. $V_A = 1.5 \times V_R$ typical |

Electrical Specifications

| Parameters | Values | Units | Conditions |
|--|--------|------------------|---|
| V_{FM} Max. Forward Voltage Drop (Per Leg) * See Fig. 1 (1) | 0.44 | V | @ 15A $T_J = 25^\circ\text{C}$ |
| | 0.51 | V | @ 30A |
| | 0.34 | V | @ 15A $T_J = 125^\circ\text{C}$ |
| | 0.45 | V | @ 30A |
| I_{RM} Max. Reverse Leakage Current (Per Leg) * See Fig. 2 (1) | 2 | mA | $T_J = 25^\circ\text{C}$ |
| | 183 | mA | $T_J = 125^\circ\text{C}$ $V_R = \text{rated } V_R$ |
| $V_{F(TO)}$ Threshold Voltage | 0.22 | V | $T_J = T_J \text{ max.}$ |
| r_t Forward Slope Resistance | 6.76 | m Ω | |
| C_T Max. Junction Capacitance (Per Leg) | 2840 | pF | $V_R = 5V_{DC}$, (test signal range 100Khz to 1Mhz) 25°C |
| L_S Typical Series Inductance (Per Leg) | 8.0 | nH | Measured lead to lead 5mm from package body |
| dv/dt Max. Voltage Rate of Change (Rated V_R) | 10000 | V/ μs | |

(1) Pulse Width < 300 μs , Duty Cycle < 2%

Thermal-Mechanical Specifications

| Parameters | Values | Units | Conditions |
|---|------------|--------------------|--|
| T_J Max. Junction Temperature Range | -55 to 150 | $^\circ\text{C}$ | |
| T_{stg} Max. Storage Temperature Range | -55 to 150 | $^\circ\text{C}$ | |
| R_{thJC} Max. Thermal Resistance Junction to Case (Per Leg) | 2.0 | $^\circ\text{C/W}$ | DC operation |
| R_{thJC} Max. Thermal Resistance Junction to Case (Per Package) | 1.0 | $^\circ\text{C/W}$ | DC operation |
| R_{thCS} Typical Thermal Resistance, Case to Heatsink | 0.50 | $^\circ\text{C/W}$ | Mounting surface, smooth and greased (only for TO-220) |
| wt Approximate Weight | 2(0.07) | g(oz.) | |
| T Mounting Torque | Min. | 6(5) | Kg-cm (lbf-in) |
| | Max. | 12(10) | |




Fig. 1- Max. Forward Voltage Drop Characteristics (PerLeg)




Fig. 2- Typical Values Of Reverse Current Vs. Reverse Voltage (PerLeg)




Fig. 3- Typical Junction Capacitance Vs. Reverse Voltage (PerLeg)




Fig. 4- Max. Thermal Impedance Z_{thJC} Characteristics (PerLeg)




Fig. 5 - Max. Allowable Case Temperature Vs. Average Forward Current (Per Leg)




Fig. 6 - Forward Power Loss Characteristics (Per Leg)




Fig. 7 - Max. Non-Repetitive Surge Current (Per Leg)





Fig. 8 - Unclamped Inductive Test Circuit

(2) Formula used: $T_c = T_j - (P_d + P_{d_{REV}}) \times R_{thJC}$;


P_d = Forward Power Loss = $I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$ (see Fig. 6);

$P_{d_{REV}}$ = Inverse Power Loss = $V_{R1} \times I_R (1 - D)$; $I_R @ V_{R1} = 10V$

Outline Table



Tape & Reel Information



Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 05/01