August 2011



## MMSD485B Small Signal Diode



SOD123 Color Band Denotes Cathode Top Marking: 28

## **Absolute Maximum Ratings**\* $T_A = 25^{\circ}C$ unless otherwise noted

Symbol	Parameter	Value	Units	
V <sub>RRM</sub>	Maximum Repetitive Reverse Voltage	100	V	
I <sub>F(AV)</sub>	Average Rectified Forward Current	200	mA	
I <sub>FSM</sub>	Non-repetitive Peak Forward Surge Current Pulse Width = 1.0 second Pulse Width = 1.0 microsecond	1.0 4.0	A A	
T <sub>STG</sub>	Storage Temperature Range	-55 to +150	°C	
Τ <sub>J</sub>	Operating Junction Temperature	150	°C	

\* These ratings are limiting values above which the serviceability of any semiconductor device may be impaired. **NOTES:** 

1) These ratings are based on a maximum junction temperature of 200 degrees C.

2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

## **Thermal Characteristics**

Symbol	Parameter	Value	Units
P <sub>D</sub>	Power Dissipation	400	mW
R <sub>θJA</sub>	Thermal Resistance, Junction to Ambient	312	°C/W

### **Electrical Characteristics** $T_A = 25^{\circ}C$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Max.	Units
V <sub>R</sub>	Breakdown Voltage	I <sub>R</sub> = 100μA	200		V
V <sub>F</sub>	Forward Voltage	I <sub>F</sub> = 100mA		1.0	V
۱ <sub>R</sub>	Reverse Leakage	V <sub>R</sub> = 180V V <sub>R</sub> = 180V, T <sub>A</sub> = 150°C		25 5.0	nA μA
CT	Total Capacitance	V <sub>R</sub> = 0, f = 1.0MHz		6.0	pF



#### SEMICONDUCTOR

### TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

2Cool™
AccuPower™
Auto-SPM™
AX-CAP™*
BitSiC <sup>®</sup>
Build it Now™
CorePLUS™
CorePOWER™
CROSSVOLT™
CTL™
Current Transfer Logic™
DEUXPEED®
Dual Cool™
EcoSPARK <sup>®</sup>
EfficientMax™
ESBC™
<b>F</b> ®
T

Fairchild<sup>®</sup> Fairchild Semiconductor<sup>®</sup> FACT Quiet Series<sup>™</sup> FACT<sup>®</sup> FAST<sup>®</sup> FastvCore<sup>™</sup> FETBench<sup>™</sup>

FPS™ F-PFS™ **FRFET**® Global Power Resource<sup>SM</sup> Green FPS™ Green FPS™ e-Series™ Gmax™ GTO™ IntelliMAX™ ISOPLANAR™ Making Small Speakers Sound Louder and Better™ MegaBuck™ MICROCOUPLER™ MicroFFT™ MicroPak™ MicroPak2™ MillerDrive™ MotionMax™ Motion-SPM™ mWSaver™ OptoHiT™ OPTOLOGIC<sup>®</sup> OPTOPLANAR<sup>®</sup>

FlashWriter®\*

PDP SPM™ Power-SPM™ PowerTrench<sup>®</sup> PowerXS™ Programmable Active Droop™ QFET QS™ Quiet Series™ RapidConfigure™  $\bigcirc$ <sup>m</sup> Saving our world, 1mW/W/kW at a time™ SignalWise™ SmartMax™ SMART START™ Solutions for Your Success™ SPM<sup>®</sup> **STEALTH™** SuperFET SuperSOT™-3 SuperSOT™-6 SuperSOT™-8 SupreMOS<sup>®</sup> SyncFET™

Sync-Lock™ SYSTEM GENERAL®∗ The Power Franchise<sup>®</sup>

# franchise

tranchise
tranchise
TinyBoost™
TinyBoost™
TinyCalc™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPWM™
TinyWire™
TransiC®
TriFault Detect™
TRUECURRENT®\*
µSerDes™



UHC<sup>∞</sup> Ultra FRFET™ UniFET™ VCX™ VisualMax™ XS™

\* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS ON OT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

### As used herein:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

### ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to protect substandard performance, failed Distributors who are listed by country on our web page cited above. Products customers buy either firectly from Fairchild or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

### PRODUCT STATUS DEFINITIONS

<b>Datasheet Identification</b>	Product Status	Definition	
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.	
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.	
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.	
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.	
		Rev. 156	

www.fairchildsemi.com