

# New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.  
SPRINGFIELD, NEW JERSEY 07081  
U.S.A.

TELEPHONE: (973) 376-2922  
(212) 227-6005  
FAX: (973) 376-8960

2N6306  
2N6307  
2N6308

## NPN Silicon Transistor

T0-3

### MAXIMUM RATINGS (T=25°C)

		2N6306	2N6307	2N6308
Collector-Emitter Voltage	V <sub>CEO</sub>	250V	300V	350V
Collector-Base Voltage	V <sub>CB0</sub>	500V	600V	700V
Emitter-Base Voltage	V <sub>EB0</sub>		8V	
Collector Current	I <sub>C</sub>		8A	
Base Current	I <sub>B</sub>		4A	
Power Dissipation	P <sub>T</sub>		125W	
Operating & Storage Junction Temperature	T <sub>J</sub> , T <sub>stg</sub>		-65 to +200°C	

### ELECTRICAL CHARACTERISTICS (T=25°C)

Symbol	Test Conditions	2N6306		2N6307		2N6308		Unit
		Min	Max	Min	Max	Min	Max	
I <sub>CEV</sub>	V <sub>CE</sub> =rated V <sub>CB</sub> , V <sub>EB</sub> =1.5V		500		500		500	uA
I <sub>CEO</sub>	V <sub>CE</sub> =rated V <sub>CEO</sub>		500		500		500	uA
I <sub>EBO</sub>	V <sub>EB</sub> =8V		1.0		1.0		1.0	mA
V <sub>CEO</sub>	I <sub>C</sub> =100mA	250		300		350		V
V <sub>CE(s)</sub>	I <sub>C</sub> =3A, I <sub>B</sub> =0.6A		0.8		1.0		1.5	V
V <sub>CE(s)</sub>	I <sub>C</sub> =8A, I <sub>B</sub> =2A		5.0		5.0			V
V <sub>CE(s)</sub>	I <sub>C</sub> =8A, I <sub>B</sub> =2.67A						5.0	V
V <sub>BE(s)</sub>	I <sub>C</sub> =8A, I <sub>B</sub> =2A		2.3		2.3			V
V <sub>BE(s)</sub>	I <sub>C</sub> =8A, I <sub>B</sub> =2.67A						2.5	V
V <sub>BE(on)</sub>	V <sub>CE</sub> =5V, I <sub>C</sub> =3A		1.3		1.3		1.5	V
h <sub>FE</sub>	V <sub>CE</sub> =5V, I <sub>C</sub> =3A	15	75	15	75	12	60	-
h <sub>FE</sub>	V <sub>CE</sub> =5V, I <sub>C</sub> =8A	4		4		3		-
f <sub>T</sub>	V <sub>CE</sub> =10V, I <sub>C</sub> =0.3A, f=1.0 MHZ	5		5		5		MHZ
C <sub>ob</sub>	V <sub>CB</sub> =10V, f=1.0 MHZ		250		250		250	pF
t <sub>r</sub>	V <sub>CC</sub> =125V, I <sub>C</sub> =3.0A, I <sub>B</sub> =0.6A		0.6		0.6		0.6	uS
t <sub>s</sub>	V <sub>CC</sub> =125V, I <sub>C</sub> =3.0A, I <sub>B</sub> =0.6A		1.6		1.6		1.6	uS
t <sub>f</sub>	V <sub>CC</sub> =125V, I <sub>C</sub> =3.0A, I <sub>B</sub> =0.6A		0.4		0.4		0.4	uS



NJ Semi-Conductors reserves the right to change test conditions, parameters limits and package dimensions without notice information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

**Quality Semi-Conductors**